AUDAC

Features

- High-fidelity, full range reproduction of music and speech
- Coverage pattern 90° x 60°
- Vertical of Horizontal coverage
- 12 Built-in rigging points
- Stand fitting built in bottom
- Scratch-free EPDM coating

Applications

- Concerts
- Clubs
- Pubs
- Indoor festivals
- Atheletic fields
- Events

AUDAC's PX108 cabinet is a compact, full range loudspeaker designed to be used especially in indoor installations.

It delivers a clear and natural sound. The loudspeaker has a 8" cone driver and a 1" HF driver with a coverage pattern of $90^{\circ} \times 60^{\circ}$ and is designed to work vertically as well as horizontally.

Average power handling is 150 W. On-axis frequency range is 95Hz to 18kHz. On-axis sensitivity (1W/1m) is 95 dB SPL and even reaches a maximum SPL of 117 dB.

For extra safety, there's a protection circuit placed inside to protect the 1" tweeter when overload occurs.

The PX series have a MDF wooden enclosure with scratch free, durable textured EPDM black painting and ergo grips.

The built-in bottom 35 mm speaker stand adapter can be replaced by a M10 screw flange.

With M10 screw flange attachment points on top and bottom, the PX108 can be mounted in any direction with an optional suspension bracket.

With the 12 rigging points on every side of the speaker, it's also possible to let him fly.

At the back of the PX108, there are two Speakon NL4MP Neutrik connectors. One of these two Speakon connectors can be used for linking a second PX108 to the first one.

Optional accessoires:

- CPB108P Cover bag
- MBK108 Wall bracket



PX108

Speaker Cabinet

► Specifications

SYSTEM SPECIFICATIONS	200 \\/	
Max power	300 W	
RMS power	150 W	
Impedance speaker	8 Ohm	
Sound pressure 1W/1m	95 dB	
Sound pressure Max W/1m	117 dB	
Frequency response -3dB	95 Hz - 18 kHz	
Frequency range -10dB	70 Hz - 20 kHz	
Cross-over frequency	2.5 kHz	
Crossover network	Passive built-in	
Horizontal coverage	90°	
Vertical coverage	60°	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	290 x 505 x 300 mm	
Weight net	14 Kg	
Drivers	HF 1" / MF 8"	
Connectors	2 x Speakon NL4MP Neutrik	
Construction	Medium density wood with EPDM black coating	
Front finish	Perforated steel grill	
Rigging flying points	12 x M10	
Carry handles	One at the side	
Rigging stand fitting	Built-in bottom 35 mm + M10 screw flange	
Colour	Black (RAL9005)	PX108/B
	White (RAL9010)	PX108/W
SHIPPING & ORDERING	,	
Packaging	Carton box	
Shipping weight & volume	16 Kg - 0.075 Cbm	
Accessories	CPB108P Protective cover bag	
	MBK108 wall bracket + Safety	

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products