



CS624

Ceiling Speaker

► Features

- High-quality 2-way ceiling speaker
- 100V Line transformer with power taps for 60W, 30W, 15W and 7.5W
- High power, wide frequency response and low distortion
- Wide coverage
- True-to-nature sound reproduction
- Quick and simple mounting

► Applications

- Public buildings
- Business offices
- Restaurants
- Warehouses
- Shops
- Hotels

The CS series loudspeakers are AUDAC's ceiling speakers, designed for use in any possible application. Wherever sound is needed without obvious speakers, or in larger buildings where the sound has to be spread over an enormous space, the CS Series speakers will offer the best solution.

The use of high quality components, combined with the application of a standard 100V line transformer, makes the CS series a range of speakers that can be used in any 100V PA system ranging from small residential installations to large business offices, shops, hotels or many more applications.

The CS624 is a high quality ceiling speaker for installation purposes with a power of 60 Watt. It consists of a 2-Way loudspeaker unit existing of a 6.5" LF loudspeaker unit, combined with an 1" dome tweeter providing premium performance in background, foreground and music-paging sound systems.

It's high power handling, wide frequency response and low distortion make the CS624 ideal for sound systems requiring a higher fidelity from ceiling loudspeakers. The premium performance capability ensures an excellent sound character, providing pleasant enveloping sound throughout the listening area.

The connections should be made by means of a 4-pin Euro-terminal block connector, allowing linkthrough to other loudspeakers. And the line transformer power tap selection can be made by using the recessed rotary switch.

The grill of the speaker can be painted, to blend in with the loudspeakers environment.



► Specifications

SYSTEM SPECIFICATIONS		
Max. power		120 W
RMS power		60 W
Line transformer power taps		60 Watt / 167 Ohm
		30 Watt / 333 Ohm
		15 Watt / 667 Ohm
		7.5 Watt / 1333 Ohm
Frequency response -3dB		65 Hz - 20 KHz
Sensitivity 1W/1m		87 dB SPL
PRODUCT FEATURES		
Dimensions (Diameter x Depth)		250 x 210 mm
Weight net		3.1 Kg
Drivers (Coaxial)	HF	1"
	LF	6.5"
Construction		ABS housing with steel firedome
Mounting		4 Screws clamps
Cut-out measurement		225 mm
Built-in depth		200 mm
Front finish		White steel grill
Connections		4-Pin Euro-Terminal Block
Power tap selection		Rotary switch behind front grill
Colour		White (RAL 9010)
SHIPPING & ORDERING		
Packaging		Carton box
Shipping weight & volume		4.1 Kg - 0.030 Cbm
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		