



HM150

Handheld Microphone

► Features

- Omnidirectional
- Push to talk switch
- Switch contact for operation with chime modules
- Metal mounting clip included
- 5-pin XLR connector

► Applications

- Warehouses
- Retail stores
- All paging applications



The HM150 is a sturdy dynamic CB type hand-held microphone with an omnidirectional pickup characteristic.

It features an easy to use Push To Talk switch on its side which makes it perfectly suited for paging messages and announcements in applications such as warehouses and shops.

While pressing the 2-pole non-latching Push To Talk switch, the microphone is switched ON and the contact for operation with chime modules is simultaneously activated.

The switch contacts for the operation of chime modules are connected on Pins 4 and 5 of the 5-pin XLR, while Pin 1(GND), Pin 2 (Sig +) and Pin 3 (Sig -) are used for the balanced microphone output signal.

A metal mounting clip is provided with the microphone.

► Specifications

SYSTEM SPECIFICATIONS	
Type	Dynamic
Polar Pattern	Cardiod
Impedance	300 Ohm
Frequency response	50 Hz - 18 kHz
Sensitivity	-75 dB ± 3dB
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	60 x 100 x 50 mm
Voice coil	Copper
Weight net	200 g
Construction	ABS
Connector	5-pin XLR (Audio + Contact)
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight	100 g
Accessory included	Metal mounting clip
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	