

► Features

- Dynamic cardioid gooseneck microphone
- Slim design
- 3 position switch
- RC network for operation with chime modules

► Applications

- Conference rooms
- Warehouses
- Professional offices
- Shops



The PDM100 paging microphone is a polyvalent dynamic gooseneck microphone, mounted on a solid, very stable base and fitted with a three function switch.

The functions are:

- Permanently on
- Momentary on
- Off

It's also equipped with a RC network for the operation of chime modules.

It's a microphone that's suitable for making announcements in big area's like conference places, warehouses, professional offices, shops, ...

A connection cable with a length of 1.5m is attached.

► Specifications

SYSTEM SPECIFICATIONS	
Frequency response	80 Hz - 12 kHz
Sensitivity	-70 dB
Impedance microphone	600 Ohm
PRODUCT FEATURES	
Dimensions	110 x 365 x 160 mm
Weight net	846 g
Connector	3-pin XLR
Connection cable length	1.5 m
Polar Pattern	Cardioid
Microphone type	Dynamic
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & Volume	2.5 Kg - 0.0065 Cbm
Accessories	MC50 Microphone windshield
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	