Wall Speaker


AUDAC

Features

- Powerful 2 way wall speaker
- True-to-nature sound reproduction
- Available in 3 different colours
- Vertical or horizontal mounting
- Mounting bracket is included
- Easy installation
- Aluminium grill
- Adjustable power tapping

Applications

- Wide variation of indoor applications
- Private houses
- Halls, Pubs
- Restaurants
- Stores
- Warehouses



They WX802 has a 8" low frequency loudspeaker and a 1" dome tweeter and is built in a synthetic enclosure which makes the speaker suitable for all purposes.

The speaker is suitable for standard home indoor installations to specialized indoor design appliances.

Due to the construction, the speaker can be mounted vertically or horizontally, using the included wall bracket.

This loudspeaker is available in three colours: white, black and silver, and is standard delivered with a wall fixig bracket in the same colour as the speaker.

By means of a recessed adjuster screw at the rear the power can be set in 3 adjustable steps of impedance for 100V and 1 step for 16 Ohm standard low impedance applications.

- 60 Watt, 30 Watt, 15 Watt @ 100V
- 70 Watt @ 16 Ohm



▶ Specifications

SYSTEM SPEC	JIFICATIONS	140 \\
Max. power		140 W
RMS power		70 W
Line Transformer Power Tap 1		60 W / 165 Ohm
Line Transformer Power Tap 2		30 W / 330 Ohm
Line Transformer Power Tap 3		15 W / 660 Ohm
Frequency Response -3dB		60 Hz - 17 KHz
Frequency Range -10dB		50 Hz - 20 KHz
Crossover frequency		2.4 KHz
Sensitivity 1W / 1m		89 dB
SPL max W / 1m @ 8 Ohm		108 dB
SPL max W / 1m @ 100 Volt		106 dB
Impedance		16 Ohm
Crossover		Passive built-in
Horizontal coverage		100°
Vertical coverage		100°
PRODUCT FEA	ATURES	
Dimensions (Width x Height x Depth)		h) 270 x 360 x 215 mm
Weight net		7.5 Kg
Drivers	HF	1"
	LF	8"
Construction		ABS housing
Mounting		Mounting bracket
Front finish		Aluminium grill
Connectors		Cable clamps
Colour		White (RAL 9010) WX802/W
		Black (RAL 9005) WX802/B
		Silver (RAL 9006) WX802/S
SHIPPING & O	RDERING	
Packaging		Carton box
Shipping weight & volume		15 Kg - 0.0636 Cbm
Accessory included		Mounting bracket

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our product